

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards | SDS Revision: 4.3

SDS Revision Date: 3/4/2016

	1. PRODUCT INDENTIFICATION
1.1	Product Name: Gel Cleanse
	Chemical Name: Isopropanol acetone mixture
	Synonyms: NA
	Trade Names: none
	Product Use: PROFESSIONAL USE ONLY
1.6	Manufacturer's Name: Ugly Duckling Nails Inc.
1.7	Manufacturer's Adress: #102-1830 Island Highway, Victoria BC, Canada V9B 1J2
1.8	Emergency Phone: (800) 535-5053 (US, Canada & Mexico) - (352) 323-3500 (International)
1.9	Business Phone / Fax:

# 2. HAZARD INDENTIFICATION

2.1 Hazard Identification:

> This product is classified as a HAZARDOUS SUBSTANCE and as a DANGEROUS GOOD according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H): H225 - Highly flammable liquid and vapor. H317 - May cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P223 - Keep container tightly closed. P243 - Take precaustionary measures against static discharge. P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaiminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - ilf eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).





2.2 Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES

2.3 Effects of Exposure:

> INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression.

EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye

> inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin reactions

(e.g., rashes, welts, dermatitis) upon prolonged or repeated expsoure.

INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give some warning of

exposure but odor fatigue may occur.

2.4 Symptoms of Overexposure:

Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure.

Acute Health Effects:

Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.

2.6 Chronic Health Effects:

The material may cause an allergic reaction for some sensitive individuals.

2.7 Target Organs:

Eyes, skin

		3. COMF	POSITION 8	& INGRE	DIENT	INF	ORM	ATIO	N					2
					EXPO:	SURE L	IMITS I	N AIR (	mg/m3	3)				
					AC	GIH		NOHSC	, ,		OSHA			
					pp	m		ppm			ppm			
							ES-	ES-	ES-					
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER	
ISOPROPANOL	67-63-0	NT8050000	200-661-7	60-100	400	500	400	500	NF	400	NA	#####	NIOSH	
	Flamm.Lig.2; Eye Ir	rit. 2; STOT SE	3, H225, H31	.9, H336										
ACETONE	67-64-1	AL3150000	200-662-2	3-10	500	750	250	#####	NF	#####	NA	#####		
		<u>-</u>		-										

	ACETONE	67-64-1	AL31500	000 200-662-2	2 3-10	500 750 250	#####   NF   #####   NA	#####	
		<u> </u>				145 4611056			
				4. FIR	SIAID	MEASURES			
4.1	First Aid:								
	INGESTION:	If ingested, d	lo not induce v	omiting! If pro	duct has be	en swallowed, drink p	olenty of water or milk IMI	MEDIATELY	7. If the patient
		is vomiting, c	ontinue to off	er water or mil	k. Never giv	ve water or milk to an	unconscious person. Con	tact the no	earest Poison
		<b>Control Cent</b>	er or local eme	ergency numbe	er. Provide	an estimate of the tim	e at which the material wa	as ingested	d and the
		amount of th	e substance th	nat was swallo	wed.				
	SKIN & EYES:	If product ge	ts in the eyes,	flush with cop	ious amour	nts of lukewarm water	for at least 15 minutes. C	Open and o	close eyelid(s)
		to ensure th	orough irrigatio	on. Seek imme	diate medic	al attention. If proble	m persists, seek immedia	te medical	attention. If
		irritation occ	urs & product i	is on the skin,	rinse thoro	ughly with lukewarm v	vater followed by a thorou	ugh washir	ng of the
		affected area	with plenty o	f soak and was	ter. Remov	e all contaminated clo	thing including footwear	and wash f	thoroughly
		before reuse	e. If irritation, r	edness or swe	elling persis	ts, consult a physician	immediately.		
	INHALATION:	Remove victi	m to fresh air a	at once. If brea	athing stops	, perform artificial res	piration. Seek immediate	medical at	tention.
4.2	Medical Conditi	ons Aggravated	by Exposure:				HEALTH	i	2
				and disorders	s of the targ	et organs (eyes, skin)	FLAMMABILITY	:	3
							PHYSICAL HAZARDS		1
							PROTECTIVE EQUIPMENT		В
							FYFS SKIN		

	5. FIREFIGHTING MEASURES	3 of 8
5.1	Flashpoint & Method:	1
	12 °C (54 °F) calculated	
5.2	Autoignition Temperature:	
	NA NA	
5.3	Flammability Limits: Lower Explosive Limit (LEL): NA Upper Explosive Limit (UEL): NA	
5.4	Fire & Explosion Hazards:	
	This product is slightly flammable. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g.,	
	CO, CO2 and Nox)	
5.5	Extinguishing Methods:	
	Water, Foam, CO2, Dry Chemical	
5.6	Fire Fighting Procedures:	
	First responders should wear eye protection. Structural fire fighters must wear full protective equipment and	
	MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains,	
	bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water	
	hafara raturnian ta canica	

# 6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

# 7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 °C (122 °F).

	8. E	EXPOSURE CONTROLS & PERSONAL PROTECTION	4
8.1	Ventilation & Engineering Controls:	Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate dequipment is available (e.g., sink, safety shower, eye wash station).	econtaimination
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.	
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.	
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves.	
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.	

	9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Density:	0.79 g/ml				
9.2	Boiling Point:	82 ° C				
9.3	Melting Point:	ND				
9.4	Evaporation Rate:	2.83 (n-butyl acetate = 1.0)				
9.5	Vapor Pressure:	44 @ 25 °C				
9.6	Appearance & Color:	Clear liquid				
9.7	Odor Threashold:	NE				
9.8	Solubility:	soluble in water				
9.9	pH:	NA				
9.1	Viscosity:	approximately 5 cps				
9.1	Flash Point:	12 °C (54 °F) calculated				
9.1	Other Information:	NA				

	10. STABILITY & REACTIVITY
10	Stability: Relatively stable under ambient conditions when stored properly.
	Hazardous Decomposition Products: If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon and nitrogen).
10	Hazardous Polymerization: Will not occur.
10	Conditions to Avoid: Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.
11	Incompatable Substances: Strong oxidizers, peroxides, strong acids or alkalis.

# 12. ECOLOGICAL INFORMATION

12 Environmental Stability:

See Section 2.3

NE

Biological Exposure Indicies:

12 Physician Recommendations: Treat syptomatically

This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Butyl Acetate: K<sub>OC</sub> = 1.82. Water Solubility: 120 parts H<sub>2</sub>O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization and biodegredation. This compound's half life is 6.1 hours.

- 12 Effects on Plants & Animals:
  - There is no specific data availble for this product on plant life.
- 12 Effects on Aquatic Life:
  - There is no specific data availble for this product on aquatic life.

## 13. DISPOSAL CONSIDERATIONS

13 Waste Disposal:

Dispose inaccordance with local, state and Federal waste laws.

13 Special Considerations:

This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations.

## 14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.

14 49 CFR (GRD):

CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) - UNTIL 12/31/2020

UN1993. FLAMMABLE LIQUID. N.O.S. (ISOPROPANOL. ACETONE). 3. II. LTD OTY (IP VOL  $\leq$  1.0 L)

14 IATA (AIR):

ID8000, CONSUMER COMMODITY, 9 (IP VOL  $\leq$  0.5 L)

UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, ACETONE). 3, II, LTD QTY (IP VOL ≤ 1.0 L)

14 IMDG (OCN):

UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, ACETONE). 3, II, LTD QTY (IP VOL ≤ 1.0 L)

14 TDGR (Canadian GND):

MARK PACKAGE "LIMITED QUANTITY" OR "QUANTITE LIMUTEE" OR "LTD QTY" OR "QUANT LTEE" (IP VOL ≤ 1.0 L) UN1170, ETHANOL SOLUTION, 3, II, LTD QTY (IP VOL > 1.0 L)

15 | ADR/RID (EU):

UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, ACETONE). 3, II, LTD QTY (IP VOL ≤ 1.0 L)

15 MEXICO (SCT):

UN1193 LIQUIDO INFLAMABLES, N.E.P. (ISOPROPANOL, ACETONA), 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L)

15 ADGR (AUS):

UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, ACETONE). 3, II, LTD QTY (IP VOL ≤ 1.0 L)



15 SARA Reporting:

NA

15 SARA Threshold Planning Quantity:

NA

15 TSCA Inventory Status:

All components of this product are listed in the TSCA Inventory or are exempt

15 CERCLA Reportable Quantity (RQ):

Isopropanol: 5,0000 lbs (2,270 kg)

16 Other Federal Requirements:

This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

16 Other Canadian Regulations:

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are on the Priorities Substances List.





16 State Regulatory Information:

No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists:

California Proposition 65 (CA), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous

Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances list, (MN), New Jersey Right-to-Know List (NJ), new Yord Hazardous Substances List (NY), Pennsylvania Right-to-Know list (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI)

16 67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements:

The primary cononents of this product are not listed in Annex 1 of EU Directive 67/548/EEC.

Isopropanol: Flammable (F). Harmful (Xi).

Risk Phrases (R): 11-36/37/38 - Highly Flammable. Irritating to eyes, skin and respiratory system. Safety Phrases (S): 2-23-29 - Keep out of reach of Children. Do not breath gas, fumes, vapor or spray. Do not empty into drains. Keep away from sources of ignition - No Smoking. Avoid contact with skin and eyes, rinse immediately with plenty of water and seek medical advice.





# **16. OTHER INFORMATION**

16 Other Information:

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - get medical advice/attention. Do not take internally. Keep away from heat and open flame. KEEP OUT OF THE REACH OF CHILDREN.

16 Terms & Definitions:

Please see last page of this SDS.

16 Disclaimer:

This Safety Data Sheet (SDS) is offered persuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Ugly Duckling Nails Inc's knowledge, the information contained herein is reliable and accurate as of the date it was prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16 Prepared for:

Ugly Duckling Nails Inc. #102-1830 Island Highway, Victoria, BC Canada V9B 1J2 (250) 590-5977

17 Prepared by:

Ugly Duckling Nails Inc. #102-1830 Island Highway, Victoria, BC Canada V9B 1J2 (250) 590-5977 Ugly Duckling



# **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### GENERAL INFORMATION:

	CAS No.	Chemical Abstract Service Number
--	---------	----------------------------------

## EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists	
TLV	Threshold Limit Value	
OSHA	U.S. Occupational Safety and Health Administration	_
PEL	Permissible Exposure Limit	Т
IDLH	Immediately Dangerous to Life and Health	_

#### FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has
 stopped receives manual chest compressions and breathing to circulate blood

## HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


## HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



#### PERSONAL PROTECTION RATINGS:

Α		
В		
С		
D		
E		
F		









Full Face Respirator







(B)













OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

## NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

## HAZARD RATINGS:

0	Minimal Hazard	
- 1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	
W	Use No Water	
OX	Oxidizer	
TREFOIL	Radioactive	



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TDio	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>io</sub> , LD <sub>io</sub> , & LD <sub>o</sub> or TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	U.S. Department of Transportation	
TC	Transport Canada	
EPA	U.S. Environmental Protection Agency	
DSL	Canadian Domestic Substance List	
NDSL	Canadian Non-Domestic Substance List	
PSL	Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act	
EU	European Union (European Union Directive 67/548/EEC)	
WGK	Wassergefährdungsklassen (German Water Hazard Class)	

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(</b>	<b>(a)</b>	<b>②</b>	①	<b>®</b>		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

## EC (67/548/EEC) INFORMATION:

E		M	*		<b>9</b>	×	×
С	Е	F	N	0	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	irritant	Harmful

## CLP/GHS (1272/2008/EC) PICTOGRAMS:

<b>\rightarrow</b>	<b>③</b>	<b>③</b>	$\Diamond$	<b></b>	<b></b>	<b></b>	<b>③</b>	<b>(</b>
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment